
QUELSTOP FIRE BATT



QuelStop Fire Batt is a coated mineral wool board used to reinstate the fire rating of wall and floor constructions where they have been penetrated by services.





QuelStop Fire Batt used in conjunction with QuelStop Intumescent Acrylic Sealant

FEATURES & BENEFITS

- Up to 2 hour fire rating
- Suitable for use in flexible walls, rigid walls and floors
- Suitable for use around cables, cable bunches, cable trays, cable ladders and non-combustible pipes
- Also suitable for use around plastic pipes and insulated non-combustible pipes with the addition of other Quelfire products
- Can be used as a blank seal as a head of wall detail.

STANDARDS & APPROVALS

- Fire resistance testing to BS EN 1366-3:2009
- EI30, EI90, EI120
- Q Classified to EN 13501-2: 2007 + A1: 2009
- Acoustic tested to EN 10140 to 60dB





SIZE

1200mm x 600mm, 50mm thick, 140kg/m³ density

APPLICATION

QuelStop Fire Batts are cut and friction fitted into the aperture with all edges and cuts sealed with the QuelStop Intumescent Acoustic Acrylic Sealant, All surfaces must be clean and free of any bond breaking contamination prior to application of the QuelStop Fire Batt and QuelStop Intumescent Acoustic Acrylic Sealant.

Additional products, including the QuelStop HPE Intumescent Graphite Sealant, the QuelCoil Continuous Intuwrap and the QWR CE Marked Fire Collars should be used in conjunction with the QuelStop Fire Batt depending on the type of penetrating services. Refer to the relevant product datasheet(s) for more information on these products.

QUELSTOP FIRE BATT





QuelStop Fire Batt used in conjunction with QuelStop HPE Intumescent Graphite Sealant

Pattress fitted QuelStop Fire Batt used in conjunction with QuelCoil Continuous Intuwrap

INSTALLATION WITHIN THE FLOOR **OR WALL APERTURE:**

Ensure that the QuelStop Fire Batt is friction fitted within the aperture and coat all joints and interfaces of the QuelStop Fire Batt using QuelStop Intumescent Acoustic Acrylic Sealant. Then finish off the edges with a bead of QuelStop Intumescent Acoustic Acrylic Sealant to create a seal.

INSTALLATION - PATTRESS FIT TO WALLS:

Ensure that you install the QuelStop Fire Batt with at least 75mm overlap and fix it to the substrate with the minimum 80mm steel screws and penny washers at maximum 300mm centres overcoated with QuelStop Coating. Coat all joints using QuelStop Intumescent Acoustic Acrylic Sealant and ensure all leading edges of the QuelStop Fire Batt are coated with QuelStop Intumescent Acoustic Acrylic Sealant.

SAMPLE SPECIFICATION

Install QuelStop Fire Batt to provide up to 2 hours fire protection where compartment walls and floors have been penetrated by services. Installation to be in accordance with manufacturer's instructions.

TECHNICAL SUPPORT & GUIDANCE

Should you require any further information regarding this product, please don't hesitate to contact one of our specialists.



QuelStop Fire Batt used in conjunction with QuelStop HPE Intumescent Graphite Sealant around the pipes

WARRANTY The Company warrants its products to be free from defects in material and workmanship for a period of 12 months from the date of delivery. The Company's obligation under this warranty is limited, as its option, to the repair or replacement, free of charge, or refund of the net Invoiced price of any part found to be defective, and which, in the Company's opinion, has not been subject to undue wear and tear, accident, alteration, abuse or misuse. Consequent damages are expressly disclaimed. Technical advice from Quelfire whether verbal, in writing or by way of trials, is given in good faith but without warranty. The application, use and installation of the Company's products are beyond the control of the Company, and the purchaser is solely responsible that goods are fit for any particular purpose. In line with the Company's policy of continual research and development, product specifications and availability are subject to change or withdrawal without prior notice.

Quelfire maintain a policy of constant improvement and reserve the right to alter or amend the specifications of their products without notice. Quelfire is a Registered Trademark.